Technical data sheet

Junction box B 9 T, perforation membrane, empty, metric

PP

Polypropylene

Item number: 2001853





The B9/T... wet-room junction box comprises two different halogen-free plastic components, 2 additional entries in base with push-through membrane

(for cable diameter up to 15 mm)

with perforation membrane (for cable diameters up to 15 mm) in the floor area.

Where cable glands are used (giving additional strain relief) there is no need to remove the membrane (this saves time). Protection rating IP67 with perforation membrane and with cable gland without the removal of the perforation membrane.

Nominal voltage 400 V; nominal cross-section 4 ÷ 6 mm²

The cover is secured with 4 pre-fitted, captured quick cover fastenings (180°) and can be sealed.

The fastening holes are additionally moulded with a soft plastic component, for a 5 mm bolt diameter (75 mm spacing). Clear internal dimensions 98x98x40 B9/T M empty: 2 fixing screw caps and 1 fixing screw plug



Master data

| Item number | 2001853 |
|---------------------------------------|-------------------------|
| Description 1 | Junction box |
| Manufacturer | OBO |
| Dimension | 110x110x50 |
| Colour | Light grey; RAL 7035 |
| Material | Polypropylene |
| Smallest sales unit | 5 |
| Unit of quantity | Piece |
| Weight | 13.1 kg |
| Weight unit | kg/100 pc. |
| CO Footprint (GWP) Cradle-to- Gate | 1,5904 kg COe / 1 Piece |

Technical data sheet

Junction box B 9 T, perforation membrane, empty, metric

Item number: 2001853





Technical data

| Expandable | |
|--------------------------------|---|
| | yes |
| No. of entries | 9 |
| Type of insertion | Cable/gland |
| Type of entry | Cable |
| Type of housing penetration | Thread and sealing membrane |
| Measured insulation voltage Vi | 400 V |
| Cover | Not transparent |
| Cover fastening | Screwed |
| Entry from rear | yes |
| Entries | 2 additional entries in base with push-through membrane(for cable diameter up to 15 mm) |
| Explosion-tested version | no |
| Flame-resistant | Acc. to VDE 0471/DIN 695 Part 2-1, test temperature 750°C |
| Shape | Square |
| Maintain electrical functions | Without |
| For Ex zone | Without |
| For Ex zone gas | Without |
| For Ex zone dust | Without |
| Halogen-free | yes |
| Clear internal dimensions | 98x98x40 mm |
| Max. Conductor cross-section | 6 mm ² |
| with lid | yes |
| Mounting type | Wall/ceiling mounting |
| Nominal cross-section, max. | 6 mm ² |
| Nominal cross-section, min. | 4 mm ² |
| Nominal voltage | 400 V |
| Sealable | yes |

Technical data sheet

Junction box B 9 T, perforation membrane, empty, metric

Item number: 2001853



Technical data

| Protection rating | IP67 |
|-----------------------------------|-------|
| Permitted temperature range, max. | 60 °C |
| Permitted temperature range, min. | -5 °C |
| Weatherproof | no |