Technical data sheet Mounting/branch piece 60 A4

Item number: 6042379



Add-on tee for the creation of a horizontal branch or cross-over, fitting for lock and screw-on cable trays of side height 60 mm. Screwless mounting with double clamps or screw connection with FRS truss-head screws and M6 combination nuts. Can be used indoors and outdoors. Fastening material must be ordered separately.





Bright, treated

2B


Master data

Item number6042379TypeRAA 640 A4Description 1Add-on teeDescription 2for cable trayManufacturerOBODimension60x400MaterialStainless steelSurfaceBright, treatedSmallest sales unit1Unit of quantityPiece		
Description 1Add-on teeDescription 2for cable trayManufacturerOBODimension60x400MaterialStainless steelSurfaceBright, treatedSurface standard1	Item number	6042379
Description 2for cable trayManufacturerOBODimension60x400MaterialStainless steelSurfaceBright, treatedSurface standard1	Туре	RAA 640 A4
ManufacturerOBODimension60x400MaterialStainless steelSurfaceBright, treatedSurface standard1	Description 1	Add-on tee
Dimension 60x400 Material Stainless steel Surface Bright, treated Surface standard 1	Description 2	for cable tray
Material Stainless steel Surface Bright, treated Surface standard 1	Manufacturer	OBO
Surface Bright, treated Surface standard Bright, treated Smallest sales unit 1	Dimension	60x400
Surface standard Smallest sales unit 1	Material	Stainless steel
Smallest sales unit 1	Surface	Bright, treated
	Surface standard	
Unit of quantity Piece	Smallest sales unit	1
	Unit of quantity	Piece
Weight 68.1 kg	Weight	68.1 kg
Weight unit kg/100 pc.	Weight unit	kg/100 pc.

Technical data sheet Mounting/branch piece 60 A4

Item number: 6042379





Width	400 mm
Height	60 mm
Plate thickness	1 mm
Dimension B	400 mm

Technical data

Departing width	400 mm
Connector version	Integrated connector
Maintain electrical functions	yes
Material thickness, floor plate	1 mm
NATO hole pattern	no
Rustproof steel, pickled	no
Permitted temperature range, max.	120 °C
Permitted temperature range, min.	-20 °C
Wide-span version	no
Type of connector, cable support system	Screwed
Recommended quantity of bolts	22 St.
Rail thickness	1.25 mm